

CB

EP 940619



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G02B 6/44	A1	(11) International Publication Number: WO 98/08124
		(43) International Publication Date: 26 February 1998 (26.02.98)
(21) International Application Number: PCT/BR97/00041 (22) International Filing Date: 13 August 1997 (13.08.97) (30) Priority Data: 9604130-7 21 August 1996 (21.08.96) BR (71) Applicant (for all designated States except US): PIRELLI CABOS S.A. [BR/BR]; Avenida Alexandre de Gusmão, 145, CEP-09110-900 Santo André, SP (BR). (72) Inventors; and (75) Inventors/Applicants (for US only): DE CASTRO, Driúcio [BR/BR]; Alameda Itanhaém, 17, Sorocaba, SP (BR). CASTRO, Edison [BR/BR]; Apartamento 12, Rua Giovanni de Nardi, 87, CEP-09570-530 São Cássano do Sul, SP (BR). VALENTE GIACAGLIA, Marcelo [BR/BR]; Rua Antonio Serafim Espigares, 21, CEP-09570-530 Sorocaba, SP (BR). SCOCCO, Marco, Antonio [BR/BR]; Rodovia Hilário Ferrari Km 5,5, CEP-13320-000 Salto, SP (BR). (74) Agent: CRUZEIRO/NEWMARC PATENTES E MARCAS LTDA.; Rua Itajobi, 79, CEP-01246-010 São Paulo, SP (BR).		(81) Designated States: CA, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.
(54) Title: HIGH MECHANICAL AND HEAT PERFORMANCE OPTICAL CABLE		
(57) Abstract		
<p>It refers to a high mechanical and heat performance optical cable for aerial or underground applications, comprising optical fibers (1) housed with a dimensional clearance inside the protection polymeric tubes (2), having a filling (3), an external sheath (6), metallic elements (8), characterized by the fact of the protection tubes (2) being assembled around the central element (7) of dielectric material, on a helicoid structure, via fastenings of polymeric wires and binding (4) with helicoid shaped polymeric tapes, also having a peripheral pulling element (5), an external sheath (6) flame resistant and metallic elements (8) helically applied forming and external ring.</p> <div data-bbox="584 1155 1169 1680"> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MX	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

HIGH MECHANICAL AND HEAT PERFORMANCE
OPTICAL CABLE.

The present invention refers to an optical cable, preferably for aerial application, however it can
5 also be used underground and has a high mechanical and heat performance because of its constructive features.

The application of optical cables in aerial networks consists of the installation in electrical power distribution networks of medium and low tension or in its
10 own pole line, in urban and rural areas. In rural areas accidents frequently occur with optical cables, because of fire caused by natural or forced burning of the local vegetation and also caused by hunter's shots.

Another important aspect of aerial optical
15 cables are the installation conditions, i.e., maximum distance between poles and sag, climatic conditions, etc., which must be seriously taken into account.

Therefore, an object in the design of aerial optical cables is to meet the mentioned installation
20 conditions, as well as, when necessary, withstand the heat conditions caused by the mentioned fires or the mechanical damage caused by the hunter's guns, without damaging the fibers or altering their optical characteristics.

In the market there are different types of
25 totally dielectric aerial optical cables, which have several advantages over the traditional solutions of metallically sheathed cables, which use corrugated or smooth aluminium or steel tapes. However, principally from the resistance point of view against the fires and gun
30 shots, the dielectric solutions show a low performance and complexity in the production process.

Further, the construction of totally dielectric aerial optical cables, to be installed with large spans, requires a great number of textile pull
35 elements so as to resist the mechanical stress in the

2

climatic and more critical installation conditions (e.g. maximum wind force, minimum temperature, etc.). This excessive number of textile elements, as well as offering difficulties in the cable's manufacturing cycle, it
5 increases the unit weight as well as the cable's outside diameter, making its dimensions more critical.

An alternative of high efficiency and proven through various practical applications, is the use of lightning conductors optical cables (OPGW). These OPGW
10 cables have exceptional optical and mechanical characteristics, since they have around their dielectric nucleus, where the optical fibers are housed, an aluminium tube and over it one or more layers of metallic wires.

These cables are preferably indicated for
15 new aerial installations in power transmission lines or replacing conventional lightning conductor cable, offering one of the highest security coefficients against accidents caused by different factors, including fire and gun shot.

These cables also have been used in
20 distribution networks or their own pole lines, to take advantages of their exceptional optical and mechanical features. However, for these installations, this alternative is not always the best solution from the economical point of view.

As a result, the present invention provides
25 an alternative which is technically and economically viable of an aerial optical cable project, so as to assure that the mentioned optical cable works according to the project's conditions and, therefore, guaranteeing the
30 mechanical and optical integrity of the optical fibers, within the foreseen mechanical stress and temperature limits. It also shows a better performance regarding heat requirements caused by fires, as well as the impacts caused by gun shots.

35 To better understand the present invention,

3

it will now be explained based on the attached drawing, which is an embodiment of the mentioned optical cable.

There are various structures used to house and protect the optical fibers, forming the optical cable nucleus. One of the structures most used is called loose tube type structure or fibers loose within a tube.

One or more optical fibers 1 are housed inside a polymeric tube 2, which has a dimensional clearance in relation with the optical fiber beam 1, that will result in a cross free play of the fibers.

The dimensions of this tube 2 and the relative length of fiber 1 in its interior, in relation with the length of the tube 2, are parameters which are estimated so as to meet the requirements of the lengthening and contraction of the optical cable.

To form the optical nucleus, these tubes are gathered on a central element 7, which can be manufactured of various materials and, usually, work as the strengthening member or mechanical support. When the optical cable has metallic elements on its outside, these central elements 7 must be of dielectric material, in order to avoid electrical discharges. The gathering of the tubes 2 on the mentioned central elements 7 can be screw-shaped, forming an open or close propeller, this technique is called SZ gathering.

This screw-shaped structure gives the fibers 1 a radial movement margin, because of the lengthenings or contractions of the optical cable.

On the tube structure 2 gathered around the central element 7, usually polymeric wire fastenings and binding 4 with polymeric tapes, also screw-shaped, are used and they assure stability of the structure and the linking of the tubes 2 to the said central element 7.

To protect the fibers from contact with humidity, the loose tubes 2 and the interstitial areas 3

are filled with a viscous polymeric gel. However, the present invention also provides the use of a dry nucleus, i.e., with no gel filling in the interstitial area 3 of the loose tubes 2, which are still kept filled so as to protect the optical fibers 1.

In this case, to protect the optical nucleus, against water penetration and spreading in these interstitial areas 3, it is an object of the present invention to use water superabsorbent elements. These materia can be used on the central element 7 and on the gathered tubes 2, in order to block all the possible routes. One of the ways of use, which must not be considered the only one, is the use of a longitudinal wire applied on the central element 7, positioned under the gathered tubes 2, and a tape helically applied on the optical nucleus.

One of the advantages of having a dry nucleus is minimizing the weight of the cable, as well as the internal pressure caused by the filling gel, originated by the increase in temperature, in the possible situations in which this occurs.

To offer better features regarding mechanical traction, these cables can be reinforced by the use of elements such as high pull textile wires, which are strung over the optical nucleus or laid longitudinally on the sheath.

As an external protection for this central nucleus, called the cable's optical nucleus, additional protections are applied which can only be dielectric of polymeric materials, metallic or compounds of metallic (typically aluminium or steel) and polymeric material. Each type of material or compound is used to offer specific features to the cables for specific applications.

In the present invention, the optical cable nucleus is totally dielectric, being coated by one or more

5
layers of polymeric material and the outermost is flame resistant. Further it is possible to use heat resistant material bindings, such as polyaramide or fiber glass tapes.

5 To attain a better performance of the cable under fire and heat requirements, as well as against impacts caused by guns, according to the above mentioned, the present invention provides the application over this flame resistant coated nucleus of metallic elements 8
10 helically applied, forming an external ring.

These metallic elements can be manufactured of various materials, such as aluminium, steel, aluminium coated steel (alclad), etc., and can have various shapes, such as cylindrical, rectangular, trapezoidal, etc.

15 When this metallic frame is applied on the coated nucleus, techniques can be used to assure its better adhesion on the polymeric coating, amongst them the use of adhesives or heat process can be mentioned.

The said metallic frame is preferably also
20 responsible for the cable's mechanical support in the most critical conditions of installation and climatic conditions, in order to optimize the design, from the cost/benefit point of view.

The use of this optical cable in aerial
25 networks, does not have any kind of special requirement during the installation and operational phases, therefore, it is an efficient alternative for the available solutions.

The present invention also can be applied in underground installation, inside tubing or directly
30 buried, having as an advantage an effective protection against the attack from rodents, a typical problem of dielectric cables.

Although the preferred embodiments of the present invention have been described and illustrated, it
35 is obvious to those specialized in the art that several


WO 98/08124

PCT/BR97/00041

modifications can be applied without forgetting the
principles of the invention.

CLAIMS

1. A high mechanical and heat performance optical cable for aerial or underground applications, comprising optical fibers (1) housed with a dimensional clearance inside the protection polymeric tubes (2), having a filling (3), an external sheath (6), metallic elements (8), characterized by the fact of the protection tubes (2) being assembled around the central element (7) of dielectric material, on a helicoid structure, via fastenings of polymeric wires and binding (4) with helicoid shaped polymeric tapes, also having a peripheral pulling element (5), an external sheath (6) flame resistant and metallic elements (8) helically applied forming an external ring.
2. An optical cable according to claim 1, characterized by also providing the use of water superabsorbent elements in the interstitial areas (3) forming a dry nucleus.
3. An optical cable according to claim 1, characterized by providing the use of heat resistant material in the binding (4) such as polyaramide or fiber glass tapes.



INTERNATIONAL SEARCH REPORT

International application No.

PCT/BR 97/00041

A. CLASSIFICATION OF SUBJECT MATTER

IPC⁶: G 02 B 6/44

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁶: G 02 B 6/44

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPOQUE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 528 653 A1 (AMERICAN TELEPHONE AND TELEGRAPH COMP.) 24 February 1993 (24.02.93), page 3, line 13 - page 4, line 42.	1,2
A	EP 0 613 033 A1 (AT&T LTD.) 31 August 1994 (31.08.94), column 3, line 22 - column 4, line 2; column 7, line 33 - column 8, line 56.	1,3
A	EP 0 632 301 A1 (PIFELLI CAVI) 04 January 1995 (04.01.95), fig. 1-4.	1,2

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

06 November 1997 (06.11.97)

Date of mailing of the international search report

20 November 1997 (20.11.97)

Name and mailing address of the ISA/ AT
 AUSTRIAN PATENT OFFICE
 Kohlmarkt 8-10
 A-1014 Vienna
 Facsimile No. 1/53424/535

Authorized officer

Gronau

Telephone No. 1/53424/348

Form PCT/ISA/210 (second sheet) (July 1992)

Printed from Mimosa

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/BR 97/00041

In Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
EP A1 528653	24-02-93	AU A1 20697/92	25-02-93
		AU B2 642352	14-10-93
		CA AA 2073998	21-02-93
		CA C 2073998	03-01-95
		DE C0 69208562	04-04-96
		DE T2 69208562	11-07-96
		EP B1 528653	28-02-96
		JP A2 6250054	09-09-94
		US A 5133034	21-07-92
EP A1 613033	31-08-94	CA AA 2113662	27-08-94
		JP A2 6273446	20-09-94
		MX A1 9401303	31-08-94
		US A 5305411	19-04-94
EP A1 632301	04-01-95	AU A1 65915/94	12-01-95
		AU B2 671911	12-09-96
		BR A 9402211	14-03-95
		CA AA 2126436	30-12-94
		CA A 11113586	08-11-95
		DE C0 69402763	28-05-97
		DE T2 69402763	13-11-97
		EP B1 632301	23-04-97
		EP B2 2102739	01-08-97
		IL A0 108954	07-10-94
		IL A1 109954	18-02-97
		IL A0 93501498	29-06-94
		IT B1 1264900	17-10-96
		IT A2 7027652	01-01-98
		JP A 2260809	06-07-96
		NZ A 2260809	03-10-95
		US A 5455881	03-10-95